

## KC19POE

Hood, Decorative wall hood, Cortina, Cream, 90 cm, A



### TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 90 cm • Extraction: Extraction • EAN code: 8017709211752

### AESTHETICS

Colour: Cream • Aesthetics: Cortina • Design: Chimney • Components finishing: Antique brass • Material: Heat-moulded • Type of steel: Brushed

### PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

### CONTROLS

Control setting: Control knobs • Control knobs: Cortina • No. of controls: 2 • Controls colour: Cream

### TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 3000 °K • Free outlet maximum capacity: 820 m³/h • Motor power: 275 W • No. of filters: 3 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEChood): 58 kWh/a • Fluid Dynamic Efficiency (FDE): 31.9 • Lighting Efficiency (LE): 83.6 lux/W • Grease Filtering Efficiency (GFE): 77.9 % • Air flow at minimum speed (Qmin): 326 m³/h • Air flow at maximum speed (Qmax): 549 m³/h • Air flow at boost speed (Qboost): 794 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 50 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 62 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 71 dB(A) • Time increase factor (F): 0.9 • Energy Efficiency Index: 53.1 • Measured air flow rate at best efficiency point (Qbep): 430 m³/h • Measured air pressure at best efficiency point (Pbep): 434 Pa • Measured electric power input at best efficiency point (Wbep): 171 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (Emiddle): 184 lux • Sound power level at highest setting (Lwa): 62 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 277 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

## SPEED 1

Extraction rate IEC 61591: 326 m³/h • Noise level IEC 60704-2-13: 50 dB(A) • Power: 199 W

## SPEED 2

Extraction rate IEC 61591: 439 m³/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 231 W

## SPEED 3

Extraction rate IEC 61591: 549 m³/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 260 W

## INTENSIVE SPEED

Extraction rate (IEC 61591): 794 m³/h • Noise level IEC 60704-2-13: 71 dB(A) • Power: 280 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 722x895x520 • Width: 895 mm • Depth (mm): 520 mm • Product Height (mm): 722 mm

## OPTIONAL

FLT6: Charcoal filter, HoodsKITKCS-2: Kit Logo & Handrail, HoodsKITKCX-2: Kit Logo & Handrail, HoodsKITALLFC: Charcoal filter, Hoods

