

KCI19AOE

Hood, Decorative island hood, Cortina, Anthracite, 90 cm, A



TYPE

Product family: Hood • Hood Type: Decorative island hood • Hood width: 90 cm • Extraction: Extraction • EAN code: 8017709212506

AESTHETICS

Colour: Anthracite • Aesthetics: Cortina • Design: Rounded • Components finishing: Antique brass • Material: Heat-moulded

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

CONTROLS

Control setting: Control knobs • Control knobs: Cortina • No. of controls: 2 • Controls colour: Anthracite

TECHNICAL FEATURES

No. of lights: 4 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 3000 °K • Free outlet maximum capacity: 820 m³/h • Motor power: 275 W • No. of filters: 3 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEChood): 59 kWh/a • Fluid Dynamic Efficiency (FDE): 25.9 • Lighting Efficiency (LE): 68.6 lux/W • Grease Filtering Efficiency (GFE): 78 % • Air flow at minimum speed (Qmin): 321 m³/h • Air flow at maximum speed (Qmax): 549 m³/h • Air flow at boost speed (Qboost): 796 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 47 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 61 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 70 dB(A) • Time increase factor (F): 0.9 • Energy Efficiency Index: 53.1 • Measured air flow rate at best efficiency point (Qbep): 426 m³/h • Measured air pressure at best efficiency point (Pbep): 453 Pa • Measured electric power input at best efficiency point (Wbep): 170 W • Nominal Power consumption of the light system (WL): 4 W • Average illumination of the light on the cooking surface (Emiddle): 302 lux • Sound power level at highest setting (Lwa): 61 dB(A)

ELECTRICAL CONNECTION

Electrical connection rating: 279 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

SPEED 1

Extraction rate IEC 61591: 321 m³/h • Noise level IEC 60704-2-13: 47 dB(A) • Power: 203 W

SPEED 2

Extraction rate IEC 61591: 385 m³/h • Noise level IEC 60704-2-13: 59 dB(A) • Power: 240 W

SPEED 3

Extraction rate IEC 61591: 549 m³/h • Noise level IEC 60704-2-13: 61 dB(A) • Power: 248 W

INTENSIVE SPEED

Extraction rate (IEC 61591): 796 m³/h • Noise level IEC 60704-2-13: 70 dB(A) • Power: 276 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 750x900x682 • Width: 900 mm • Depth (mm): 682 mm • Product Height (mm): 750 mm

ACCESSORIES INCLUDED

Tube reduction: Yes

OPTIONAL

FLT6: Charcoal filter, HoodsKITKCS: Kit Logo & Handrail, HoodsKITKCX: Kit Logo & Handrail, Hoods



